

Fraunhofer

TESTED® DEVICE

KUKA Roboter GmbH LBR iiwa 14 R820 CR **Report No. KU 1707-925**

Statement of Qualification

Particle Emission





Statement of Qualification

Customer KUKA Roboter GmbH

> Zugspitzstrasse 140 86165 Augsburg Germany

Component tested

Category: **Automation Components**

Subcategory: Robotics

LBR iiwa 14 R820 CR Product name:

(manufacturing date: 5/2017; article number: 10027479; serial number:

982697; payload: 14kg; reach: 820 mm)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines:

Test devices:

Test environment parameters:

Test procedure parameters:

ISO 14644-1, -14

The norms stated generally refer to the version valid at the time of the tests.

Optical particle counter:

LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1 \,\mu\text{m}$, $\geq 0.2 \,\mu\text{m}$, \geq 0.3 µm, \geq 0.5 µm, \geq 1.0 µm and > 5.0 µm

•	Cleanroom Air Cleanliness Class (according to ISO	14644-1):ISO 1
_	Airflow volocity:	0 1E m /c

	,	
•	Airflow pattern:	vertical laminar flow
	Temperature:	22°C+0.5°C

•	Capacity:
•	Attached payload:
•	Pause between cycles:

radic between cycles	
Operation of each axis:	separately
Manager and a fine and a series	

	operation of each anishment	separacery
•	Movement of each axis:	
	– Axis 1:	170° until 170°
	– Axis 2:	90° until 90°
	– Axis 3:	90° until 90°
	– Axis 4:	120° until 120°
	– Axis 5:	170° until 170°

– Axis 7:	175° until 175°

..-120° until 120°



- Axis 6:.

Test result/Classification

When operated under the specified test conditions, the robot LBR iiwa 14 R820 CR is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
Capacity = 40 %	2
Capacity = 80 %	2
Overall result	2



The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

For further information about the test environment and parameters, please refer to the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12 70569 Stuttgart Germany

KU 1707-925

Report No. first document

Report No. current document

on behalf of River

Stuttgart, October 12, 2017

Place, date of first document issued

This document only applies to the named product in its original state and is valid for a period of 5 years from the date the first document was issued. The document can be verified under

www.tested-device.com.