

Fraunhofer

TESTED® DEVICE

TSUBAKIMOTO CHAIN CO. TKR0200W50R55

Report No. KA 1008-531

Statement of Qualification





Statement of Qualification

Customer: TSUBAKIMOTO CHAIN CO.

1-1-3, kannabidai,

Kyotanabe, Kyoto 610-0380,

Component tested: Cable carrier

TKR0200W50R55 Type:

Tests performed: Random check measurements of particle emission (airborne) at representative points

Test parameters: • Chain length:213 cm • Stroke length:.....140 cm

• Set of parameters 1:......v,: 0.5 m/s; a,: 1.0 m/s²

• Set of parameters 2:.......v₂: 1.0 m/s; a₂: 2.0 m/s²

• Set of parameters 3:v₃: 2.0 m/s; a₂: 5.0 m/s²

Test results / classification: When the Energy Chain is being operated at the above mentioned test parameters, it is suitable for use in cleanrooms fulfilling the

Air Cleanliness Class 1 according to ISO 14644-1.

Standards/guidelines used for the qualification:

VDI 2083 Part 1, 4 and 9.1; ISO 14644-1

Test parameters of the cleanroom environment:

Cleanroom of Air Cleanliness Class ISO Class 1 (according to ISO 14644-1)

Air flow velocity: 0.45 m/s

Air flow guidance: vertical unidirectional air flow from ceiling to floor (raised floor)

Temperature: $22 ^{\circ}\text{C} \pm 0.5 ^{\circ}\text{C} (71.6 ^{\circ}\text{F} \pm 0.9 ^{\circ}\text{F})$

Relative humidity: 45 % ± 5 %

The measuring equipment used for the qualification is regularly calibrated and is based on national and international standards. In the case where no national standards exist, the measuring procedure used corresponds with technical regulations and norms valid at the time of the measurement. The documents drawn up for this procedure are available for viewing.

for Manufacturing Engineering

Nobelstrasse 12 70569 Stuttgart Germany

Fraunhofer Institute and Automation IPA

Department Ultraclean Technology and Micromanufacturing

Fraunhofer

Stuttgart, September 1, 2010