



Fraunhofer

**TESTED[®]
DEVICE**

CP SYSTEMS CO., LTD
nsb028CRG.75.R70/F
Report No. CP 1802-1008

DUPLICATE

Statement of
Qualification

Particle Emission

Statement of Qualification

Customer CP SYSTEMS CO., LTD
27-37, Jeonggwansanggok-1gil
Jeongwan-eup, Gijang-gun, Busan
Korea

Component tested

Category: Energy Supply

Subcategory: Cable Guiding Systems

Product name: New Sabin Cleanroom Gore Cable Chain nsb028CRG.75.R70/F
(manufacturing date: 3/2018; color: white and black; overall width: 94 mm;
width inside the channels: 2x12.5 mm, 2x6.3 mm, 1x16 mm; thickness
of the chain: 38.3 mm; number of channels: 5; number of cable used: 4;
diameter cable 1-4: 6.3 mm)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines: ISO 14644-1, -14
The norms stated generally refer to the version valid at the time of the tests.

Test devices: Optical particle counter:
LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1 \mu\text{m}$, $\geq 0.2 \mu\text{m}$,
 $\geq 0.3 \mu\text{m}$, $\geq 0.5 \mu\text{m}$, $\geq 1.0 \mu\text{m}$ and $\geq 5.0 \mu\text{m}$

Test environment parameters:

- Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
- Airflow velocity:.....0.45 m/s
- Airflow pattern:..... vertical laminar flow
- Temperature:22 °C \pm 0.5 °C
- Relative humidity: 45 % \pm 5 %

Test procedure parameters:

- Bending radius:r = 70 mm
- Stroke length:..... s = 820 mm
- Parameter Set 1:..... $v_1 = 0.5 \text{ m/s}$; $a_1 = 1.0 \text{ m/s}^2$
- Parameter Set 2:..... $v_2 = 1.0 \text{ m/s}$; $a_2 = 2.0 \text{ m/s}^2$
- Parameter Set 3:..... $v_3 = 2.0 \text{ m/s}$; $a_3 = 4.0 \text{ m/s}^2$

Test result / Classification

When operated under the specified test conditions, the cable system New Sabin Cleanroom Gore Cable Chain nsb028CRG.75.R70/F is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
$v_1 = 0.5 \text{ m/s}$; $a_1 = 1.0 \text{ m/s}^2$	1
$v_2 = 1.0 \text{ m/s}$; $a_2 = 2.0 \text{ m/s}^2$	1
$v_3 = 2.0 \text{ m/s}$; $a_3 = 4.0 \text{ m/s}^2$	3
Overall result	3

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

CP 1802-1008
Report No. first document

Stuttgart, June 8, 2018
Place, date of first document issued

Department of Ultraclean Technology and Micromanufacturing

--
Report No. current document

--
Place, current date

Nobelstrasse 12
70569 Stuttgart
Germany

on behalf of 
Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA