

Fraunhofer

TESTED® DEVICE

KUKA Roboter GmbH LBR iiwa 14 R820

Report No. KU 1605-829

Statement of Qualification

Particle Emission





Statement of Qualification

Customer KUKA Roboter GmbH

> Zugspitzstrasse 140 86165 Augsburg Germany

Component tested

Category: Automation component

Subcategory: Robotics

LBR iiwa 14 R820 Product name:

> (manufacturing date: 10/2015; color: white; serial number: 981816; payload: 14kg; reach: 820mm; Part of KMR iiwa 14 R820)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines:

Test devices:

Test environment parameters:

Test procedure parameters:

VDI 2083-9.1; ISO 14644-1

The norms stated generally refer to the version valid at the time of the tests.

Optical particle counter:

LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1 \,\mu\text{m}$, $\geq 0.2 \,\mu\text{m}$, \geq 0.3 μ m, \geq 0.5 μ m, \geq 1.0 μ m and > 5.0 μ m

 Cleanroom Air Cleanliness Class (according to IS 	O 14644-1):ISO 1
Airflow velocity:	0.45 m/s
Airflow pattern:	vertical laminar flow
Temperature:	22°C±0.5°C
Relative humidity:	45 % ± 5 %

•	Speed: 40	0 % and 80 %
,	Attached payload:	14 kg
•	Pause between cycles:	1 s

Pause between cycles:	1s
Operation of each axis:	separately
Movement of each axis:	

Operation of each axis:	separately
Movement of each axis:	
– Axis 1:	150° until -150°
– Axis 2:	70° until -70°
– Axis 3:	165° until -165°
– Axis 4:	70° until -70°
– Axis 5:	165° until -165°
– Axis 6:	70° until -70°
Δxis 7·	170° until -170°



Test result/Classification

When operated under the specified test conditions, the robot LBR iiwa 14 R820 is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Class according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
Workload = 40 %	3
Workload = 80 %	4
Overall result	4

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

For further information about the test environment and parameters, please refer to the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12 70569 Stuttgart Germany

Stuttgart, July 29, 2016

Place, date of first document issued

This document only applies to the named product in an unchanged state and is valid from the date of issue for a period of 5 years. The document can be verified under www.tested-device.com.