



Fraunhofer

**TESTED[®]
DEVICE**

KANEKO CORD CO., LTD.
G-FLON/UL2517-P-SB-CR AWG24
Report No. KA 1301-629

DUPLICATE

Statement of
Qualification

Statement of Qualification

Customer: KANEKO CORD CO., LTD.
80 Nakagawa Hosoe-Cho
431-1304 Hamamatu-City, Shizuoka
Japan

Test results / Classification:
(according to ISO 14644-1)

The G-FLON/UL2517-P-SB-CR AWG24 series is suitable for use in cleanrooms fulfilling Air Cleanliness Class 1.

Component tested:

Category: Energy Supply
Subcategory: Cable Systems
Type: G-FLON/UL2517-P-SB-CR AWG24 series:
• TP04: GF/2517-AWG24 x 1P-SB-CR (Manufacturing date: 01/12/2012)
• TP05: GF/2517-AWG24 x 6P-SB-CR (Manufacturing date: 01/12/2012)
• TP06: GF/2517-AWG24 x 15P-SB-CR (Manufacturing date: 01/12/2012)

Random check measurements of particle emission (airborne) at representative points

Test procedure: According to VDI 2083 Part 9.1
Measuring instruments: Optical Particle Counter:
Model LasAir II 110 manufactured by PMS with measuring channels of
0.1 µm, ≥ 0.2 µm, ≥ 0.3 µm, ≥ 0.5 µm, ≥ 1.0 µm and ≥ 5.0 µm
Test parameters of the test environment:
• Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
• Air flow velocity:..... 0.45 m/s
• Air flow guidance:vertical unidirectional air flow
• Temperature: 22 °C ± 0.5 °C (71.6 °F ± 0.9 °F)
• Relative humidity: 45 % ± 5 %
Test parameters of the test execution:
• Energy chain (reference):igus E3.15.060.032.0
• Cable length (TP04): l = 1075 mm
• Cable length (TP05): l = 1070 mm
• Cable length (TP06): l = 1070 mm
• Chain bending diameter (TP04 and TP05): d = 120 mm
• Chain bending diameter (TP06): d = 180 mm
• Stroke length: s = 820 mm
• Parameter set 1: v₁ = 0.5 m/s; a₁ = 1.0 m/s²
• Parameter set 2: v₂ = 1.0 m/s; a₂ = 2.0 m/s²
• Parameter set 3: v₃ = 2.0 m/s; a₃ = 4.0 m/s²

The measuring equipment used for the qualification is regularly calibrated and is based on national and international standards. In the case where no national standards exist, the measuring procedure used corresponds with technical regulations and norms valid at the time of the measurement. The documents drawn up for this procedure are available for viewing.

The validity of this certificate applies only to the mentioned product in this particular condition for a duration of 5 years.
Further information: www.tested-device.com.


Fraunhofer Institute for
Manufacturing Engineering and Automation IPA

Department Ultraclean Technology
and Micromanufacturing

Nobelstrasse 12
70569 Stuttgart
Germany

Stuttgart, February 14, 2013

Place, Date


i. A.
Project manager