

Fraunhofer

TESTED[®] DEVICE

Thomas Engineering Co., Ltd. PODFLEX 4 x 0.75 mm²

Report No. TH 1809-1067

Statement of Qualification

Particle Emission





Statement of Qualification

Customer Thomas Engineering Co., Ltd.

#397, Sindaeseokseong-ro, Bugi-myeon, Cheongwon-gu

28133 Cheongju-si, Chungcheongbuk-do

Republic of Korea

Component tested

Category: **Energy Supply**

Subcategory: Cable Systems

Cable PODFLEX 4 x 0.75 mm² Product name:

(manufacturing date: 7/26/2018; color: black; serial number: 3CA00118;

batch number: H-G26)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines:

Test devices:

Test environment parameters:

Test procedure parameters:

ISO 14644-1, -14

The norms stated generally refer to the version valid at the time of the tests.

Optical particle counter:

LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1 \,\mu\text{m}$, $\geq 0.2 \,\mu\text{m}$, \geq 0.3 μ m, \geq 0.5 μ m, \geq 1.0 μ m and \geq 5.0 μ m

• (Cleanroom Air	Cleanliness	Class	(according to ISO	14644-1):	. ISO 1
-----	---------------	-------------	-------	-------------------	-----------	---------

•	Airtiow	velocity:		0.45	m/s
•	Airflow	pattern:	vertical	laminar	flow

- Temperature:

•	Bending radius:	:r	= 75 mm
---	-----------------	----	---------

- Stroke length:..... • Parameter Set 1: $v_1 = 0.5 \,\text{m/s}$; $a_2 = 1.0 \,\text{m/s}^2$
- Parameter Set 2:.....v₂ = 1.0 m/s; a₂ = 2.0 m/s²

Test result/Classification

When operated under the specified test conditions, the Cable PODFLEX 4 x 0.75 mm² is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
$v_1 = 0.5 \text{m/s}; a_1 = 1.0 \text{m/s}^2$	1
$v_2 = 1.0 \text{m/s}; a_2 = 2.0 \text{m/s}^2$	1
$v_3 = 2.0 \text{m/s}; a_3 = 4.0 \text{m/s}^2$	1
Overall result	1



The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12 70569 Stuttgart Germany

TH 1809-1067

Report No. first document

Report No. current document Place, current date

on behalf of RT Bir

Stuttgart, September 17, 2018

Place, date of first document issued

This document only applies to the named product in its original state and is valid for a period of 5 years from the date the first document was issued. The document can be verified under

www.tested-device.com.

