



Fraunhofer
TESTED[®]
DEVICE
NICHIGOH CABLE
RO-FLEX I II III S 0.14 x 1P
Report No. NI 1809-1066

DUPPLICATE

Statement of
Qualification

Particle Emission

Statement of Qualification

Customer

Nichigoh Communication Electric Wire Co., Ltd.
2175-1, Uenoyorozumachi
518-0855 Iga-City, Mie
Japan

Test result / Classification

When operated under the specified test conditions, the cable system RO-FLEX I II III S 0.14 x 1P is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
$v_1 = 0.5 \text{ m/s}; a_1 = 1.0 \text{ m/s}^2$	1
$v_2 = 1.0 \text{ m/s}; a_2 = 2.0 \text{ m/s}^2$	1
$v_3 = 2.0 \text{ m/s}; a_3 = 4.0 \text{ m/s}^2$	1
Overall result	1

Component tested

Category: Energy Supply

Subcategory: Cable Systems

Product name: RO-FLEX I II III S 0.14 x 1P
(manufacturing date: 3/2018; color: black; serial number: ZZ-30075)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines:

ISO 14644-1, -14

The norms stated generally refer to the version valid at the time of the tests.

Test devices:

Optical particle counter:

LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1 \mu\text{m}$, $\geq 0.2 \mu\text{m}$, $\geq 0.3 \mu\text{m}$, $\geq 0.5 \mu\text{m}$, $\geq 1.0 \mu\text{m}$ and $\geq 5.0 \mu\text{m}$

Test environment parameters:

- Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
- Airflow velocity:..... 0.45 m/s
- Airflow pattern:..... vertical laminar flow
- Temperature: $22^\circ\text{C} \pm 0.5^\circ\text{C}$
- Relative humidity: 45 % ± 5 %

Test procedure parameters:

- Bending radius: $r = 75 \text{ mm}$
- Stroke length: $s = 820 \text{ mm}$
- Parameter Set 1: $v_1 = 0.5 \text{ m/s}; a_1 = 1.0 \text{ m/s}^2$
- Parameter Set 2: $v_2 = 1.0 \text{ m/s}; a_2 = 2.0 \text{ m/s}^2$
- Parameter Set 3: $v_3 = 2.0 \text{ m/s}; a_3 = 4.0 \text{ m/s}^2$

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing
Engineering and Automation IPA

Department of Ultraclean Technology
and Micromanufacturing

Nobelstrasse 12
70569 Stuttgart
Germany

NI 1809-1066
Report No. first document

Stuttgart, September 17, 2018
Place, date of first document issued

--
Report No. current document

--
Place, current date

on behalf of 
Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA

This document only
applies to the named
product in its original state
and is valid for a period of
5 years from the date the
first document was issued.
The document can be
verified under
www.tested-device.com.