



**Fraunhofer**

**TESTED<sup>®</sup>  
DEVICE**

J. Schmalz GmbH  
SAXM 60 ED-85 G1/4-AG  
**Report No. SC 1606-831**

DUPLICATE

Statement of  
Qualification

Particle Emission

# Statement of Qualification

**Customer**  
 J. Schmalz GmbH  
 Aacher Strasse 29  
 72293 Glatten  
 Germany

**Component tested**

Category: Process Equipment

Subcategory: Vacuum Components

Product name: Bell-shaped suction cup SAXM 60 ED-85 G1/4-AG  
 (color: blue; material code: Elastodur; article number: 10.01.19.00055;  
 material type: elastomer)

## Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines: VDI 2083-9.1; ISO 14644-1  
 The norms stated generally refer to the version valid at the time of the tests.

Test devices: Optical particle counter:  
 LasAir II 110 and LasAir III 110 with measuring ranges  $\geq 0.1 \mu\text{m}$ ,  $\geq 0.2 \mu\text{m}$ ,  
 $\geq 0.3 \mu\text{m}$ ,  $\geq 0.5 \mu\text{m}$ ,  $\geq 1.0 \mu\text{m}$  and  $\geq 5.0 \mu\text{m}$

Test environment parameters:

- Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
- Airflow velocity:.....0.45 m/s
- Airflow pattern:..... vertical laminar flow
- Temperature: .....22 °C  $\pm$  0.5 °C
- Relative humidity: ..... 45 %  $\pm$  5 %

Test procedure parameters:

- Operating pressure: ..... 6 bar (ultra-pure compressed air)
- Static absolute pressure on the gripper: ..... approx. 200 mbar
- Evacuation time:..... 12 s
- Release time: ..... 8 s
- Cycles per minute:..... 3

## Test result / Classification

When operated under the specified test conditions, the bell-shaped suction cup SAXM 60 ED-85 G1/4-AG is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Class according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
operating pressure = 6 bar (ultra-pure compressed air) evacuation time = 12 s release time = 8 s cycles per minute = 3	4
<b>Overall result</b>	<b>4</b>

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

For further information about the test environment and parameters, please refer to the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12  
 70569 Stuttgart  
 Germany

Stuttgart, October 10, 2016

Place, date of first document issued

--

Place, current date

on behalf of   
 Frank Bürger, Project Manager Fraunhofer IPA