



**Fraunhofer**

**TESTED<sup>®</sup>  
DEVICE**

Yoshinogawa Cable  
SRFV series

**Report No. YO 1510-788**

DUPLICATE

Statement of  
Qualification

Particle Emission

# Statement of Qualification

**Customer** Yoshinogawa Electric Wire & Cable Co., Ltd.  
331, Omore-Cho  
761-0493 Takamatsu-shi, Kagawa  
Japan

**Component tested**

Category: Energy Supply

Subcategory: Cable Systems

Product name: SRFV series (manufacturing date: 9/2015; color: black)  
test objects:  
SRFV-A021P01S (Lot No.: 2015091719-2);  
SRFV-A021P15S (Lot No.: 2015091705-5);  
SRFV-A030P15S (Lot No.: 2015091705-6);  
SRFV-A050P04S (Lot No.: 2015091705-3);  
SRFV-A050P15S (Lot No.: 2015092403-2);  
SRFV-A075C02S (Lot No.: 2015091705-2);  
SRFV-A075C20S (Lot No.: 2015092403-1);  
SRFV-A125C06S (Lot No.: 2015091705-4);  
SRFV-A125C20S (Lot No.: 2015092403-3)

## Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines: VDI 2083-9.1; ISO 14644-1  
The norms stated generally refer to the version valid at the time of the tests.

Test devices: Optical particle counter:  
LasAir II and LasAir III 110 with measuring ranges  $\geq 0.1 \mu\text{m}$ ,  $\geq 0.2 \mu\text{m}$ ,  
 $\geq 0.3 \mu\text{m}$ ,  $\geq 0.5 \mu\text{m}$ ,  $\geq 1.0 \mu\text{m}$  and  $\geq 5.0 \mu\text{m}$

Test environment parameters:

- Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
- Airflow velocity:.....0.45 m/s
- Airflow pattern:..... vertical laminar flow
- Temperature: .....22 °C  $\pm$  0.5 °C
- Relative humidity: ..... 45 %  $\pm$  5 %

Test procedure parameters:

- Energy chains:..... igus E61.29.050.075.0/igus E61.29.050.100.0/igus  
..... E61.29.050.150.0
- Chain bending radii:..... r = 75 mm to 180 mm
- Stroke length:..... s = 820 mm
- Cable lengths: ..... l = 845 mm to 1130 mm
- Parameter Set 1:..... $v_1 = 0.5 \text{ m/s}$ ;  $a_1 = 1.0 \text{ m/s}^2$
- Parameter Set 2:..... $v_2 = 1.0 \text{ m/s}$ ;  $a_2 = 2.0 \text{ m/s}^2$
- Parameter Set 3:..... $v_3 = 2.0 \text{ m/s}$ ;  $a_3 = 4.0 \text{ m/s}^2$

## Test result / Classification

When operated under the specified test conditions, the cable system series SRFV is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Class according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
$v_1 = 0.5 \text{ m/s}$ ; $a_1 = 1.0 \text{ m/s}^2$	4
$v_2 = 1.0 \text{ m/s}$ ; $a_2 = 2.0 \text{ m/s}^2$	1
$v_3 = 2.0 \text{ m/s}$ ; $a_3 = 4.0 \text{ m/s}^2$	4
<b>Overall result</b>	<b>4</b>

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

For further information about the test environment and parameters, please refer to the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12  
70569 Stuttgart  
Germany

Stuttgart, February 20, 2016

Place, date of first document issued

--

Place, current date

on behalf of   
Frank Bürger, Project Manager Fraunhofer IPA