



Fraunhofer

**TESTED[®]
DEVICE**

ZORN Maschinenbau GmbH
ZLAG1-100-Z

Report No. ZO 1608-844

DUPLICATE

Statement of
Qualification

Particle Emission

Statement of Qualification

Customer
 ZORN Maschinenbau GmbH
 Höllstrasse 11
 78333 Stockach
 Germany

Component tested

Category: Automation component

Subcategory: Linear Units

Product name: Zorn linear axis ZLAG1-100-Z
 (manufacturing date: 7/2016; material: aluminum natural anodized;
 serial number: 1607-00007)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines: VDI 2083-9.1; ISO 14644-1
 The norms stated generally refer to the version valid at the time of the tests.

Test devices: Optical particle counter:
 LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1 \mu\text{m}$, $\geq 0.2 \mu\text{m}$,
 $\geq 0.3 \mu\text{m}$, $\geq 0.5 \mu\text{m}$, $\geq 1.0 \mu\text{m}$ and $\geq 5.0 \mu\text{m}$

Test environment parameters:

- Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
- Airflow velocity:.....0.45 m/s
- Airflow pattern:..... vertical laminar flow
- Temperature:22 °C \pm 0.5 °C
- Relative humidity: 45 % \pm 5 %

Test procedure parameters:

- Installation position:vertical
- Travel length:..... s = 85 mm
- Test load:.....none
- Parameter Set 1:..... $v_1 = 0.5 \text{ m/s}$; $a_1 = 1.0 \text{ m/s}^2$
- Parameter Set 2:..... $v_2 = 1.0 \text{ m/s}$; $a_2 = 2.0 \text{ m/s}^2$
- Parameter Set 3:..... $v_3 = 2.0 \text{ m/s}$; $a_3 = 4.0 \text{ m/s}^2$

Test result / Classification

When operated under the specified test conditions, the Zorn linear axis ZLAG1-100-Z is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Class according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
$v_1 = 0.5 \text{ m/s}$; $a_1 = 1.0 \text{ m/s}^2$	5
$v_2 = 1.0 \text{ m/s}$; $a_2 = 2.0 \text{ m/s}^2$	6
$v_3 = 2.0 \text{ m/s}$; $a_3 = 4.0 \text{ m/s}^2$	6
Overall result	6

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

For further information about the test environment and parameters, please refer to the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12
 70569 Stuttgart
 Germany

Stuttgart, September 14, 2016

Place, date of first document issued

--

Place, current date

on behalf of 
 Frank Bürger, Project Manager Fraunhofer IPA