



# Fraunhofer

## TESTED<sup>®</sup> DEVICE

KUKA Deutschland GmbH  
LBR iisy 11 R1300 CR  
**Report No. KU 2303-1404**

Statement of  
Qualification

Single product  
Outgassing Behavior  
Ammonia

Statement of Qualification · Single product

Customer	KUKA Deutschland GmbH Zugspitzstrasse 140 86165 Augsburg Germany
Component tested	
Category:	Automation Components
Subcategory:	Robotics
Product name:	LBR iisy 11 R1300 CR (manufacturing date: 1/10/2024; color: white and orange; weight: 46.3 kg; serial number: 4561014)

Emission chamber measurements with impingement in combination with ion chromatography (IC)

Standards/Guidelines:	ISO 14644-8, -15; VDI 2083 Part 17; VDI 2452 Part 1 (impinger); ISO 14911 (cations) The norms stated generally refer to the version valid at the time of the tests.
Testing equipment:	<ul style="list-style-type: none"><li>Measuring station:.....Metrohm Professional IC 850</li><li>Sampling chamber:.....Markes International µCTE</li></ul>
Sample storage:	<ul style="list-style-type: none"><li>Pre-conditioning:<ul style="list-style-type: none"><li>Cleanroom Air Cleanliness Class (according to ISO 14644-1):.....ISO 1</li><li>Airflow velocity:.....0.45 m/s</li><li>Airflow type:.....vertical laminar flow</li><li>Temperature: .....22 °C ± 0.5 °C</li><li>Relative humidity: .....45 % ± 5 %</li><li>Purified air: .....VOC-filtered</li></ul></li></ul>
Test procedure parameters:	Outgassing test temperature: .....23 °C

Test result / Classification

The outgassing behavior of the robot LBR iisy 11 R1300 CR at rest the stated temperature was investigated according to VDI 2083 Part 17 and ISO 14644-15. Based on the outgassing rates determined for the specific units, the following material classification was made for the corresponding Contaminant Category:

Contaminat Category (x)	SER <sub>u</sub> <sup>1)</sup> 23 °C [g/unit · s]	ISO-ACC <sub>e</sub> Class (x) based on 23 °C
Ammonia (NH <sub>3</sub> )	< 7.0 x 10 <sup>-9</sup>	< -8.2

<sup>1)</sup>SER<sub>u</sub>: Unit-specific emission rate

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.



Fraunhofer Institute for Manufacturing Engineering and Automation IPA  
  
Department of Ultraclean Technology and Micromanufacturing  
  
Nobelstrasse 12  
70569 Stuttgart  
Germany

KU 2303-1404	Stuttgart, May 22, 2024
Report No. first document	Place, date of first document issued
--	--
Report No. current document	Place, current date
on behalf of	
Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA	

This document only applies to the named product in its original state and is valid for a period of 5 years from the date the first document was issued. The document can be verified under [www.tested-device.com](http://www.tested-device.com).