



Fraunhofer

TESTED[®] DEVICE

ABB
IRB 1200-8/0.9 Gen2
Report No. AB 2506-1634

DUPLICATE

Statement of
Qualification

Single product
Particle Emission
in Cleanroom
(atmospheric)

Customer	ABB Engineering (Shanghai) Ltd. No.39, MiaoQiao Road, Pudong New District 201319 Shanghai China
Tested product	
Category:	Automation Components
Subcategory:	Robotics
Product name:	IRB 1200-8/0.9 Gen2 (manufacturing date: 3/27/2025; color: white; weight: 44kg; serial number: 1200-CR0001)

Random sampling of particle emissions (airborne) at representative sites in cleanroom under atmospheric conditions

Standards/guidelines:	ISO 14644-1, -14 The norms stated generally refer to the version valid at the time of the tests.
Test equipment:	Optical particle counter: LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1\text{ }\mu\text{m}$, $\geq 0.2\text{ }\mu\text{m}$, $\geq 0.3\text{ }\mu\text{m}$, $\geq 0.5\text{ }\mu\text{m}$, $\geq 1.0\text{ }\mu\text{m}$ and $\geq 5.0\text{ }\mu\text{m}$
Test environment parameters:	<ul style="list-style-type: none">Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1Airflow velocity:.....0.45 m/sAirflow pattern:..... vertical laminar flowRoom temperature:22 °C ± 0.5 °CRelative humidity: 45 % ± 5 %
Test procedure parameters:	<ul style="list-style-type: none">Capacity:50 % and 100 % of maximum velocityAttached payload: 8 kgPause between cycles: 1 to 3 sOperation of each axis:..... separatelyMovement of each axis:<ul style="list-style-type: none">– Axis J1: -220° to 220°– Axis J2: -100° to 100°– Axis J3: -200° to 70°– Axis J4: -230° to 230°– Axis J5: -130° to 130°– Axis J6: -400° to 400°

Test result / Classification	The robot IRB 1200-8/0.9 Gen2 is suitable for use under the specified test parameters (room temperature: 22 °C ± 0.5 °C; relative humidity: 45 % ± 5 %) in cleanrooms of the following Air Cleanliness Classes according to ISO 14644-1:
------------------------------	--

Test parameter(s)	Air Cleanlines Class
50 % of maximum velocity	4
100 % of maximum velocity	4
Overall result	4

Please note: Transport damages, incorrect installation, oil leakage, aging behavior, corrosion etc. can influence the test result.

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA	AB 2506-1634 Report No. first document	Stuttgart, June 25, 2025 Place, date of first document issued
Business unit Testing and Certification	-- Report No. current document	-- Place, current date
Nobelstrasse 12 70569 Stuttgart Germany	on behalf of Dr.-Ing. Frank Bürger, head of business unit Testing and Certification	