



Fraunhofer

TESTED[®]
DEVICE

KUKA

KR SCARA_KR 12 R650 Z340 CR

Report No. KU 2204-1316

Statement of
Qualification

Single product
Particle Emission

Statement of Qualification · Single product

Customer	KUKA Robotics Guangdong Co., Ltd. No.3, Liaoxin Road, Shuikou Residential Committee, Beijiao Town, Shunde District, Foshan City 528311, Guangdong Province China
Component tested	
Category:	Automation Components
Subcategory:	Robotics
Product name:	KR SCARA_KR 12 R650 Z340 CR (manufacturing date: 2/2022; color: white; weight: 54 kg; serial number: 10037902; batch number: 8630236)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines:	ISO 14644-1, -14 The norms stated generally refer to the version valid at the time of the tests.
Test devices:	Optical particle counter: LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1\text{ }\mu\text{m}$, $\geq 0.2\text{ }\mu\text{m}$, $\geq 0.3\text{ }\mu\text{m}$, $\geq 0.5\text{ }\mu\text{m}$, $\geq 1.0\text{ }\mu\text{m}$ and $\geq 5.0\text{ }\mu\text{m}$
Test environment parameters:	<ul style="list-style-type: none">Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1Airflow velocity:.....0.45 m/sAirflow pattern:..... vertical laminar flowTemperature:22 °C \pm 0.5 °CRelative humidity: 45 % \pm 5 %
Test procedure parameters:	<ul style="list-style-type: none">Capacity:50 % and 100 % of maximum velocityAttached payload: 6 kgPause between cycles:1 sOperation of each axis:..... separatelyMovement of each axis:<ul style="list-style-type: none">– Axis 1: -100° to 100°– Axis 2: -100° to 100°– Axis 3: -355° to 0°– Axis 4: -350° to 350°

Test result / Classification

When operated under the specified test conditions, the robot KR SCARA_KR 12 R650 Z340 CR is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanlines Class
50 % of maximum velocity	6
100 % of maximum velocity	6
Overall result	6

Please note: Transport damages, incorrect installation, oil leakage, aging behavior, corrosion etc. can influence the test result.


The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12
70569 Stuttgart
Germany

KU 2204-1316	Stuttgart, November 14, 2022
Report No. first document	Place, date of first document issued
--	--
Report No. current document	Place, current date
on behalf of	
Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA	



This document only applies to the named product in its original state and is valid for a period of 5 years from the date the first document was issued. The document can be verified under www.tested-device.com.